

Minifors

TR Series Specifications

Portable and powerful for unlimited heights of lift

- A complete range of electric hoists for a wide range of applications
- Rated loads of 220 lbs, 660 lbs, and 1,000 lbs which can be doubled by a sheave kit
- Unlimited height of lift
- Unloaded wire rope freely suspended or optional rope reeler
- Pendant control
- Direct lift or sheaving kit for increased capacity
- Single phase or 3 phase power

Quality & Power

- High power to weight ratio
- Body in aluminum alloy
- Unlimited length of lifting wire rope
- Wire rope, dia. 0.25 in. (6.5 mm)
- 110V standard, 220V available

Safety

- Upper and lower adjustable end limit stops
- Motor integrated brake

TR50/TR30S



TR30



Minifor® fitted with wire rope reeler (optional)



Minifor® TR10-TR30 Kit



Specifications

Model	Dimensions L x W x D (in.)	Weight without Wire Rope lbs. (kg)	WLL lbs. (kg)		Speed fpm (mpm)		Power Supply			Optional WR Reeler	
			Direct	Sheaved	Direct	Sheaved	Single Phase 115 V	Single Phase 220 V	Three Phase 220 V	66 ft. 20 m	100 ft. 35 m
TR10	14 x 9 x 17	46 (20)	220 (100)	441 (200)	50 (15)	25 (7.5)	u	u		u	u
TR30	14 x 9 x 17	46 (20)	660 (300)	1,320 (600)	17 (5)	8.5 (2.5)	u	u		u	u
TR30S	19 x 9 x 17	71 (32)	660 (300)	1,320 (600)	43 (13)	21 (6.5)	u	u	u		
TR50	19 x 9 x 17	71 (32)	1,000 (453)	2,000 (906)	23 (7)	11.5 (3.5)	u	u	u		

Green shading reflects rental inventory.