

Rol-A-Lifts

1 Ton - 6 Ton Model Specifications

M-4 Rol-A-Lift



- Top clamps to secure narrow or heavy loads.
- Side belts to stabilize load and prevent slippage during movement.
- Under the load belt secures load.
- Polyurethane casters in single or dual wheel for floor protection and weight distribution.
- All Models available in wide versions.
- 4 position swivel locks are available on all casters.

Specifications													
Model	Cap. Per Pair (lbs)	Max. Hydraulic Lift (in)	Standard wheels	Wheel Size (in)	Overall ht. (in)	Overall width (in)	Caster Centers (in)	Overall depth (in)	Forks Adjustable (in)	Fork Length (in)	Fork Thickness (in)	Weight (lbs)	
M-2	2,000	5 1/8	Phenolic*	5 x 2	47 1/2	22	18	12 1/2	7 1/4-17 1/2	5	3/4	160	
M-4	4,000	12	Phenolic*	6 x 2	44	23		16 1/2	5-19 1/2		6	1 1/8	325
M-4-6	4,000-6,000	12-6	Phenolic*	6 x 2	44	23		16 3/4	6-19 1/2			1 1/8	340
M-6	6,000	6	Phenolic*	6 x 2	42 1/2	23		16 3/4	6-19 1/2	1 1/8		335	
M-8	8,000	6	Semi-Steel	8 x 2 1/2	45	23 1/8		17 1/4	7 1/4-19 1/2	1 1/8		400	
M-10	10,000	6	Semi-Steel	8 x 2 1/2	45 1/2	24		18	9 1/4-19 1/2	1 1/8	438		
M-12	12,000	6	Forged-Steel	8 x 2 1/2	45 1/2	24		18	9 1/4-19 1/2	1 1/8	470		

Green shading reflects rental inventory.

